EUROCAVE

S-INSP-S

Inspiration

Multi-temperatures cabinet | **Small size** | **Service Pack** | **5-Year warranty**

MANUFACTURÉ EN FRANCE

Built-in and flush-fitted, multi-temperatures cabinet, for serving wine



Equipment
Standard shelves



Sliding shelf
ACMSIB
6 bottles



Sliding shelf
ACMSIW
6 bottles



Sliding wine service area
ACMSERVB
11 bottles



Sliding wine service area
ACMSERVW
11 bottles



Half shelf
ACMSI-DEMI
5 bottles

Equipment
Optional shelves



Storage shelf
AXIHB
22 bottles



Storage shelf
AXIHW
22 bottles

Technical specifications

Capacity	29 bottles maximum*	
Temperature	· Default setup temperature: 8-18°C / 46-64°F · Temperature setting range from 5°C to 20°C / 41- 68°F (5-10°C/ 41-50°F for the lower part and 15-20°C/ 59-68°F for the upper part).	
Design	· 4 doors options: full glass door, stainless steel glass door, technical solid door and technical glass door (Reversible integrated glass door with soft close and door stop) · Lock (except technical door) · LED screen with backlit capacitive keys	· Amber inner lighting : atmosphere lighting with the light strip and 2 LEDs · 3 lighting options: permanent, open door, disabled) · Amber screen display
Accessories	· 2 sliding shelves with Mains du Sommelier (possible adjustment of the position of the MDS, on the front) · 1 half shelf and 1 sliding wine service area · Light oak and black glossy front · Open / close locking notch	· 6 removable bottles identifiers per sliding shelf · 1 erasable felt-tip marker · 1 microfiber cloth · 1 key ring
Equipement	· Charcoal filter (with counter) · Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)	· 4 adjustable feet · Condensate drip tray at the back
Regulation	· Electronic regulation · Display of the real temperature inside the cabinet · Display standby mode, possible	· Visual alarm: carbon filter · Visual and audible alarms: temperature malfunction, sensor fault, open door · Automatic defrost
Technologies	**Cold production:**	Static
	Cords:	CE/US/UK/JA/AU/CH/C6/CN
	Hot production:	Heating element
	Hot release:	Automatic/ threshold: adjustable
	Inner material:	Stucco aluminium
	Exterior coating material:	HDF (High Density Fiber) melamine-faced panels
	Insulation type:	PU Foam (59mm)

*Traditional Bordeaux format

General features

	Full Glass door/ stainless steel glass door	Technical glass door	Technical solid door
Empty wine cabinet net weight (kg)	54	53	50
Equipped cabinet net weight (kg)	64	63	60
Gross weight packaged (kg)	77	76	73
Dimensions H x W x D (mm)	810-880x557-594**x597	810-880x557-594**x597	810-880x557-594**x597
Dimensions packaged (mm)	980x645x630	980x645x630	980x645x630
Specific features of the decor panel		Thickness: 20mm maximum / Weight: 12kg maximum	

**With fillers

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)
Type of door	Full Glass/Glass	Technical solid door
Energy efficiency class	G	F
Annual energy consumption AEC (Kwh/year)	125	99
Sound emission (dB(A))	38	38
Sound emission Class	C	C
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95
Useful volume (litres)	94	

NB : This model is not adapted for a stand-alone installation.
To guarantee the proper functioning of the wine cabinet, the top and bottom ventilation strips must not be covered in any way.

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens…

