EUROCAVE

THE CHAMPAGNE CABINET



1-temperature cabinet | **Large size** | **5-Year warranty**

MANUFACTURÉ EN FRANCE

Single-temperature cabinet, for serving or ageing champagne

Equipment
Standard shelves




Fixed presentation shelf
APRESCHAMPG
8 bottles
12kg




Fixed presentation shelf
APRESMAGNUMG
5 bottles
10kg




Sliding presentation shelf
ACCHAMPG
8 bottles of champagne
6 magnum of champagne
4.8kg



Presentation LUX
pack standard
1 fixed presentation shelf
+7 sliding shelves
75 bottles



Presentation LUX
pack magnum
1 fixed presentation shelf
+ 6 sliding shelves
62 bottles



Premium pack
10 sliding shelves
91 bottles

Technical specifications

Capacity	91 bottles maximum*	
Temperature	· Default setup temperature: 5°C / 41°F · Temperature setting range from 5°C / 41 to 12/54°F	
Design	· Full Glass door · Reversible door (warning on the orientation of the icotype on the handle) · Removable Full glass handle · Central lock · Champagne coloured control panel with glossy finish · White screen display	· LED screen with touch-sensitive keys · 1 ambient light, amber, blue or red (colour to be selected on order) · 3 lighting options: permanent, on door opening or off
Accessories	· 1 sliding presentation shelf, equipped with a soft close system. 8 removable bottle holders, in brushed stainless steel · 2 fixed presentation shelves (standard or magnum bottles). 8 or 5 polished stainless steel bottle holders	· Shelves with champagne-coloured lacquer fronts · Shiny leather finish to protect bottles and for more comfort of use · 1 microfibre cloth · 1 erasable felt-tip marker · 1 EuroCave keyring
Equipment	· Charcoal filter · Clay ball humidity cassette	· 2 adjustable feet at the front · Condensate drip tray at the back
Regulation	· Electronic regulation · Display of the real temperature inside the cellar · Display of the humidity when the temperature is set between 9-12°C/ 48-54°F	· Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm) · Automatic defrost
Technologies	**Cold production:**	Air fan/Compressor R600a
	Cords:	CE/US/UK/JA/AU/CH/C6
	Heat production:	Heating element
	Heatt release:	Automatic/threshold:adjustable
	Inner material:	Aluminium
	Exterior coating material:	HDF (High Density Fibreboard)
	Insulation type:	PU foam (59mm)

*Standard champagne format

THE CHAMPAGNE CABINET

General features

	Full Glass door
Gross weight packaged (kg)	96
Weight of reinforced packaging (kg)	13 (+8 kg pallet)
Dimensions H x W x D (mm)	1825 x 680 x 720**
Dimensionsin pack H x W x D	1950 x 720 x 760
Color	Nero - RAL 9005

**With rear stopper, without handle

Energy efficiency and consumption

Cords	**230V-50Hz (R600a)**	**115V-60Hz (R600a)**
Type of door	**Full Glass**	**Full Glass**
Energy efficiency class	G	G
Annual energy consumption (kWh/ year)	190	190
Sound emission (dB(A))	37	37
Sound emission class	C	C
Ambient operating temperatures (C°/°F)	0-30°C / 32-86°F	0-30°C / 32-86°F
Useful volume (litres)	461	

The champagne cabinet, in a few words...

The French way of life

The champagne cabinet is exclusively dedicated to displaying and serving champagne, it is a one-of-a-kind object. Designed to store all shapes and sizes of champagne bottles thanks to its specially designed shelves, this cabinet is a bold homage to the originality of champagne houses and their heritage.

