



Manufactured in France

1 temperature cabinet

Medium size

Access Pack



Maturing cabinet, for wine ageing

Technical Specifications

Capacity 170 bottles maximum*

Temperature · Default setup temperature: 12°C / 54°F
· Temperature setting range from 6/ 43°F à 18°C/64°F

Design · 2 door options: glass with black frame or solid with black frame
· Central lock
· Black control panel
· White interior lighting: 2 leds (ON/OFF)
· LED screen with touch-sensitive keys
· White screen display

Accessories · 4 multifunctional beechwood shelves
· Optional: set of 20 black aluminium plates + 1 erasable felt-tip marker Ref : ID20-STYLO
· 1 EuroCave keyring

Equipment · Charcoal filter
· Clay ball humidity cassette
· 2 adjustable feet at the front
· Condensate drip tray at the back

Regulation · Electronic regulation
· Display of the real temperature inside the cabinet
· Hygrometry display
· Visual alarms in case of dysfunction (open door, sensor fault, temperature alarm, charcoal filter, humidity level alarm)
· Automatic defrost

Technologies **Cold production:** Mixed air / Compressor R600a gas
Cords: CE/US/UK/JA/AU/CH/C6
Heat production: Resistance
Heat release: Automatic / Threshold: adjustabl
Inner material: Aluminium
Exterior coating material: HPL panel (High pressure laminates)
Insulation type: Injected polyurethane foam (59mm)

Equipment
Standard shelf

**Multifunctional shelf
AEPHU1**



Sliding
12 bottles



Storage
72 bottles



Sliding presentation
9 bottles



Fixed presentation
24 bottles

Equipment
**Optional shelves
(Mounted in the cabinet)**



Sliding shelf
ACMS
12 bottles



Storage shelf
AXUH
77 bottles

*Traditional Bordeaux format

General features

	Glass door	Solid door
Empty wine cabinet net weight (kg)	81	69
Equipped cabinet net weight (kg)	91	79
Gross weight packaged (kg)*	106	94
Dimensions H x W x D (mm)	1480x 680 x 720**	1480x 680 x 720**
Dimensions packaged (mm)	1605 x 720 x 760	1605 x 720 x 760
Colour	Nero - RAL 9005	Nero - RAL 9005

**Incl. the separator at the back/ 690 mm without separator. The dimensions do not include the handle.

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)		115V-60Hz (R600a)	
	Solid	Glass	Solid	Glass
Type of door				
Energy efficiency class	F	G	/	/
Annual energy consumption AEC (Kwh/year)	125	154	143	172
Sound emission (dB(A))	37	37	38	38
Sound emission Class	C	C	/	/
Ambient operating temperature (°C/°F)	0-35 / 32-95	0-30/ 32-86	0-35 / 32-95	0-30 / 32-86
Useful volume (litres)		360		

La Premiere, in a few words..

The fundamental by EuroCave.

The Première wine cabinet is designed for multiple uses. Concealed beneath its bold lines lies all the brand's expertise. Take your first steps into the world of EuroCave.

