



Manufactured in France

1 temperature cabinet

Small size

Access Pack

5 YEAR WARRANTY

Built-in and flush-fitted, 1 temperature cabinet, for ageing of wine



Equipment
Standard shelves



Sliding shelf
ACMSIB
6 bottles



Sliding shelf
ACMSIW
6 bottles



Storage shelf
AXIHB
22 bottles



Storage shelf
AXIHW
22 bottles

Equipment
Optional shelves



Sliding wine service area
ACMSERVB
11 bottles



Sliding wine service area
ACMSERVW
11 bottles



Half shelf
ACMSI-DEMI
5 bottles

Technical specifications

Capacity 30 bottles maximum*

Temperature

- Default setup temperature: 12°C/54°F
- Temperature setting range from 5°C to 20°C / 41- 68°F

Design

- 4 doors options: full glass door, stainless steel glass door, technical solid door, technical glass door (reversible integrated glass door with soft close and door stop)
- Lock (except technical door)
- LED screen with backlit capacitive keys
- Amber inner lighting: atmosphere lighting with the light strip and 2 LEDs
- 3 lighting options: permanent, open door, disabled
- Amber screen display

Accessories

- 1 sliding shelf with Mains du Sommelier (possible adjustment of the position of the MDS, on the front)
- 1 storage shelf (+grid)
- Light oak and black glossy front
- 6 removable bottles identifiers per sliding shelf
- 1 erasable felt-tip marker
- 1 microfiber cloth
- 1 key ring

Equipment

- Charcoal filter (with counter)
- Humidity cassette with clay ball
- Low-emissivity glass and argon gas between the 2 glasses (in glass door or full glass finish)
- 4 adjustable feet
- Condensate drip tray at the back

Regulation

- Electronic regulation
- Display of the real temperature inside the cabinet
- Possible humidity display
- Display standby mode, possible
- Visual and audible alarms: temperature fault, sensor fault and open door
- Visual alarms: humidity fault and carbon filter change
- Automatic defrost
- Frost protection thermostat (double protection)

Technologies

- Cold production:** Static/ Compressor R600a
- Cords:** CE/US/UK/JA/AU/CH/C6/CN
- Hot production:** Heating element
- Hot release:** Automatic/ threshold: adjustable
- Inner material:** Stucco aluminium
- Exterior coating material:** HDF (High Density Fiber) melamine-faced panels
- Insulation type:** PU Foam (59mm)

*Traditional Bordeaux format

General features

	Full Glass door	Stainless steel glass door	Technical glass door	Technical solid door
Empty wine cabinet net weight (kg)	54	54	53	50
Equipped cabinet net weight (kg)	58	59	56	53
Gross weight packaged (kg)	71	72	69	66
Dimensions H x W x D (mm)	810-880x557-594**x597	810-880x557-594**x597	810-880x557-594**x597	810-880x557-594**x597
Dimensions packaged (mm)	980x645x630	980x645x630	980x645x630	980x645x630
Specific features of the decor panel	Thickness: 20mm maximum / Weight: 12kg maximum			

**With fillers

Energy efficiency & Consumption

Cords	230V-50Hz (R600a)	230V-50Hz (R600a)	230V-50Hz (R600a)
Type of door	Full Glass door	Stainless steel glass door/ technical	Technical solid door
Energy efficiency class	G	G	F
Annual energy consumption AEC (Kwh/year)	125	125	99
Sound emission (dB(A))	38	38	38
Sound emission Class	C	C	C
Ambient operating temperature (°C/°F)	12-35/54-95	12-35/54-95	12-35/54-95
Useful volume (litres)	94		

NB : This model is not adapted for a stand-alone installation.
To guarantee the proper functioning of the wine cabinet, the top and bottom ventilation strips must not be covered in any way.

Inspiration, in a few words...

Understated & Elegant

The heart of the home, the kitchen is no longer reserved just for cooking. A place to gather and spend time together, it is open to all the family and often friends too. The kitchen has become a place where good times are shared, things are created, ideas germinate and chemistry happens...

